



					SERHQ020AAW1+SERHQ20AAW1	SERHQ020AAW1	SERHQ020AAW1+SERHQ020AAW1	SERHQ032AAW1	SERHQ032AAW1+SERHQ032AAW1
Template					Altherma Outdoor	Altherma Outdoor	Chillers air cooled	Altherma Outdoor	Chillers air cooled
Dimensions	Packed unit		Width	mm		1,055	1,055	1,365	1,365
			Height	mm		1,855	1,855	1,855	1,855
			Depth	mm		860	860	860	860
	Unit		Width	mm		930	930	1,240	1,240
			Depth	mm		765	765	765	765
			Height	mm		1,680	1,680	1,680	1,680
Compressor	Motor	Crankcase heater	Output	W		33		33	
			Quantity		1		1		
	Output		W			1,200	1,200	1,400	1,400
	Speed		rpm			6,300	6,300	6,300	6,300
	Quantity					2	2	3	3
	Compressor--Type					Hermetically sealed scroll compressor	Hermetically sealed scroll compressor	Hermetically sealed scroll compressor	Hermetically sealed scroll compressor
	Model					Inverter	Inverter	Inverter	Inverter
Casing	Colour					Daikin White	Daikin White	Daikin White	Daikin White
	Material					Painted galvanized steel plate	Painted galvanized steel plate	Painted galvanized steel plate	Painted galvanized steel plate
Fan motor	Output		W			750	750	350	350
	Quantity					1	1	2	2
	Model					Brushless DC motor	Brushless DC motor	Brushless DC motor	Brushless DC motor
Weight	Packed unit		kg			273.00	273.00	355.95	355.95
	Unit		kg			240.00	240.00	316.00	316.00
Fan	Air flow rate	Heating	Nom.	m³/min		185 (1)	185 (1)	233 (1)	233 (1)
		Cooling	Nom.	m³/min		185 (1)	185 (1)	233 (1)	233 (1)
	Quantity					1	1	2	2

	Type		Propeller fan	Propeller fan	Propeller fan	Propeller fan
	Discharge direction		Vertical	Vertical	Vertical	Vertical
Packing 3	Weight	kg	0.27		0.33	
	Material		Plastic		Plastic	
Packing	Weight	kg	4.02	4.02	6.35	6.35
	Material		Carton	Carton	Carton	Carton
Packing 2	Weight	kg	20.85		23.55	
	Material		Wood		Wood	
Heat exchanger	Passes	Quantity	18		21	
	Fin	Treatment	Hydrophilic and corrosion resistant		Hydrophilic and corrosion resistant	
		Type	Non-symmetric waffle louvre		Non-symmetric waffle louvre	
	Empty tubeplate hole	Quantity	0		0	
	Rows	Quantity	54		54	
	Face area	m²	2.11		2.48	
	Length	mm	1,778		2,088	
	Fin pitch	mm	2		2	
	Stages	Quantity	2		2	
	Tube type		ø8 Hi-XSS		ø8 Hi-XSS	
Notes	Notes--Description		230V	230V	230V	230V
Fan motor 2	Output	W			350	350