

				FTXP20K2V1B	FTXP25K2V1B	FTXP35K2V1B
Sound pressure level	Heating	High	dBA	39	40	43
		Nom.	dBA	34	34	35
	Cooling	Silent operation	dBA	23	23	26
		Low	dBA	28	28	29
		Silent operation	dBA	20	20	20
		Low	dBA	25	26	27
		High	dBA	39	40	43
		Nom.	dBA	33	33	34
Standard Accessories	Item			Installation manual	Installation manual	Installation manual
	Quantity			1	1	1
	Item			Operation manual	Operation manual	Operation manual
	Quantity			1	1	1
	Item			Wireless remote control	Wireless remote control	Wireless remote control
	Quantity			1	1	1
	Item			AAA dry-cell batteries	AAA dry-cell batteries	AAA dry-cell batteries
	Quantity			2	2	2
	Item			Remote control holder	Remote control holder	Remote control holder
	Quantity			1	1	1
	Item			Mounting plate	Mounting plate	Mounting plate
	Quantity			1	1	1
	Item			Titanium apatite photocatalytic air purification filter	Titanium apatite photocatalytic air purification filter	Titanium apatite photocatalytic air purification filter
	Quantity			2	2	2
	Item			Indoor unit fixing screws	Indoor unit fixing screws	Indoor unit fixing screws
	Quantity			2	2	2
Refrigerant	Refrigerant=Gwp			675	675	675
	Type			R-32	R-32	R-32
Control systems	Infrared remote control			ARC480A11	ARC480A11	ARC480A11
	Wired remote control			BRC944B2, BRC073A1	BRC944B2, BRC073A1	BRC944B2, BRC073A1
Fan motor	Output	Rated	W	22	22	22

	Speed	Cooling	High	rpm	980	1,020	1,140
			Medium	rpm	800	820	840
			Low	rpm	640	660	680
			Silent operation	rpm	550	550	560
		Heating	High	rpm	1,060	1,080	1,220
			Medium	rpm	860	860	900
			Low	rpm	690	710	730
			Silent operation	rpm	590	590	590
				Steps	5 + silent, + auto	5 + silent, + auto	5 + silent, + auto
	Model				MM6K11S20VA	MM6K11S20VA	MM6K11S20VA
Power input - 50Hz	Cooling		Nom.	kW	0.018	0.020	0.02
	Heating		Nom.	kW	0.022	0.023	0.03
Packing	Weight			kg	3	3	3.5
Heat exchanger	Fin			Type	ML fin (Multi louver)	ML fin (Multi louver)	ML fin (Multi louver)
	Fin pitch			mm	1.4	1.4	1.4
	Stages			Quantity	18	18	18
	Rows			Quantity	2	2	2
	Length			mm	610	610	610
	Tube type				ø5 Hi-XB	ø5 Hi-XB	ø5 Hi-XB
Piping connections	Liquid		OD	mm	6.35	6.35	6.35
	Gas		OD	mm	9.50	9.50	9.50
	Drain				18	18	18
	Heat insulation				Both liquid and gas pipes	Both liquid and gas pipes	Both liquid and gas pipes
Sound power level	Cooling			dBa	55	55	58
	Heating			dBa	55	55	58
Air filter	Type				Removable / washable / mildew proof	Removable / washable / mildew proof	Removable / washable / mildew proof
Dimensions	Packed unit		Width	mm	830	830	830
			Height	mm	305	305	305
			Depth	mm	360	360	360
	Unit		Width	mm	770	770	770
			Depth	mm	225	225	225
			Height	mm	286	286	286
Casing	Colour				White	White	White
Weight	Packed unit			kg	11	11	11.5
	Unit			kg	8	8	8

Fan	Air flow rate	Heating	Low	cfm	226	237	237
			High	m³/min	10.9	11.1	12.8
			Low	m³/min	6.4	6.7	6.9
			Silent operation	cfm	184	184	184
			Nom.	cfm	300	300	304
			Silent operation	m³/min	5.2	5.2	5.2
			High	cfm	385	392	427
			Nom.	m³/min	8.5	8.5	8.5
		Cooling	Low	m³/min	5.8	6.1	6.3
			Nom.	m³/min	7.8	8.0	8.2
			Low	cfm	205	215	219
			Silent operation	cfm	170	170	170
			Nom.	cfm	275	283	279
			High	m³/min	9.9	10.4	11.8
			High	cfm	350	367	399
			Silent operation	m³/min	4.8	4.8	4.9
	Type				Cross flow fan	Cross flow fan	Cross flow fan
Template					Split Sky Air Indoor	Split Sky Air Indoor	Split Sky Air Indoor
Air direction control					Right, Left, Horizontal, Downward	Right, Left, Horizontal, Downward	Right, Left, Horizontal, Downward
Temperature control					Microcomputer control	Microcomputer control	Microcomputer control
Power supply	Frequency			Hz	50	50	50
	Voltage			V	220-240	220-240	220-240
	Phase				1~	1~	1~
Current	Nominal running current (RLA) - 50Hz		Heating	A	0.21	0.22	0.24
			Cooling	A	0.18	0.20	0.20
Notes	Notes--Description				SL: The silent fan level of the air flow rate setting	SL: The silent fan level of the air flow rate setting	SL: The silent fan level of the air flow rate setting
Heat exchanger 2	Stages			Quantity			4
	Length			mm			600
	Rows			Quantity			1
	Fin pitch			mm			1.40