

				FLXS25BAVMB / RXS25L3V1B
Poff (Off mode)	W			14.0
Cooling	Psb (Standby mode cooling)		W	14.0
Cooling==Cooling cdc degradation cooling				0.25
Moisture removal	Cooling		l/h	1.2
Seasonal efficiency (according to EN14825)	Cooling	Pdesign	kW	2.50
		Annual energy consumption	kWh	169
			Seasonal efficiency (according to EN14825)-=-Cooling==Seasonal efficiency according to en14825 cooling energy label	A
			Seasonal efficiency (according to EN14825)-=-Cooling==Seasonal efficiency according to en14825 cooling seer	5.19
	D Condition (20°C - 27/19)	Pdc	kW	1.44
		power input	kW	0.14
			Seasonal efficiency (according to EN14825)-=-Cooling==D Condition (20°C - 27/19)-=-Eerd	10.56
	C Condition (25°C - 27/19)	power input	kW	0.16
		Pdc	kW	1.36
			Seasonal efficiency (according to EN14825)-=-Cooling==C Condition (25°C -	8.40

			27/19)-== Eerd	
	A Condition (35°C - 27/19)	power input	kW	0.67
		Pdc	kW	2.50
			Seasonal efficiency (according to EN14825)-== Cooling)-=A Condition (35°C - 27/19)-== Eerd	3.74
	B Condition (30°C - 27/19)	Pdc	kW	1.84
		power input	kW	0.31
			Seasonal efficiency (according to EN14825)-== Cooling)-=B Condition (30°C - 27/19)-== Eerd	5.96
	Heating (Average climate)	Annual energy consumption	kWh	921
		Pdesign	kW	2.50
		Required back up heating cap at design conditions	kW	0.33
			Seasonal efficiency (according to EN14825)-== Heating (Average climate)-= Seasonal efficiency according to en14825 heating average climate scop	3.80
			Seasonal efficiency (according to EN14825)-== Heating (Average climate)-= Seasonal efficiency according to en14825 heating average climate scopnet	3.87

			Seasonal efficiency (according to EN14825)-=- Heating (Average climate)-=- Seasonal efficiency according to en14825 heating average climate energy label	A
	TBivalent	Pdh (declared heating cap)	kW	2.21
		Power input	kW	0.95
		Tbiv (bivalent temperature)	°C	-7
			Seasonal efficiency (according to EN14825)-=- Heating (Average climate)-=- TBivalent=- Copd declared cop	2.33
	C Condition (7°C)	Pdh (declared heating cap)	kW	1.10
		Power input	kW	0.22
			Seasonal efficiency (according to EN14825)-=- Heating (Average climate)-=- C Condition (7°C)-=- Copd declared cop	4.94
	TOL	Tol (temperature operating limit)	°C	-15
		Pdh (declared heating cap)	kW	2.10
		Power input	kW	1.09
			Seasonal efficiency (according to EN14825)-=- Heating (Average climate)-=- TOL=- Copd declared cop	1.92
	A Condition (-7°C)	Pdh (declared heating cap)	kW	2.21
		Power input	kW	0.95

			Seasonal efficiency (according to EN14825)-= Heating (Average climate)-=A Condition (-7°C)-= Copd declared cop	2.33
	D Condition (12°C)	Pdh (declared heating cap)	kW	1.28
		Power input	kW	0.20
			Seasonal efficiency (according to EN14825)-= Heating (Average climate)-=D Condition (12°C)-= Copd declared cop	6.25
	B Condition (2°C)	Power input	kW	0.34
		Pdh (declared heating cap)	kW	1.35
			Seasonal efficiency (according to EN14825)-= Heating (Average climate)-=B Condition (2°C)-=Copd declared cop	4.02
Cooling capacity	Nom.		Btu/h	8,500 (2)
	Min.		kW	1.2
	Nom.		kcal/h	2,150 (2)
	Max.		kW	3.0
	Min.		kcal/h	1,030
	Min.		Btu/h	4,100
	Nom.		kW	2.5 (2)
	Max.		Btu/h	10,200
	Max.		kcal/h	2,580
Pck (Crankcase heater mode)	W			0.0
Nominal efficiency	Annual energy consumption		kWh	334
	Energy label		Heating	B
			Cooling	A

	Nominal efficiency--Cop			3.54 (1)
	Nominal efficiency--Eer			3.74 (1)
Heating	Heating--Heating cdh degradation heating			0.25
Piping connections	Liquid	OD	mm	6.35
	Gas	OD	mm	9.5
	Drain	OD	mm	18.0
	Heat insulation			Both liquid and gas pipes
Heating capacity	Min.		Btu/h	4,100
	Nom.		Btu/h	11,600 (2)
	Max.		kcal/h	3,870
	Max.		Btu/h	15,400
	Nom.		kW	3.4 (2)
	Min.		kW	1.2
	Nom.		kcal/h	2,920 (2)
	Min.		kcal/h	1,030
	Max.		kW	4.5
	Pto (Thermostat off)	W		
Power input	Cooling	Min.	kW	0.300
		Nom.	kW	0.668 (2)
		Max.	kW	0.860
	Heating	Max.	kW	1.490
		Min.	kW	0.290
		Nom.	kW	0.960 (2)
Template				Split Sky Air Set
Indoor unit				FLXS25B
Outdoor unit				RXS25L3
Cold season included				no
Average climate included				yes
Warm season included				no
Heating function included				yes
Ecolabel logo				no
Cooling function included				yes
Current	Nominal running current (RLA) - 50Hz	Heating	A	4.70 (3), 4.50 (4), 4.30 (5)
		Cooling	A	3.80 (3), 3.70 (4), 3.49 (5)
Notes				EER/COP according to Eurovent 2012, for use outside

	EU only
	Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load
	220V
	230V
	240V