

					CTXS15K2V1B	CTXS15K3V1B	CTXS35K3V1B	CTXS35K2V1B
Sound pressure level	Heating		High	dBA	38	38	41	41
			Nom.	dBA	33	33	36	36
			Silent operation	dBA	21	21	21	21
			Low	dBA	28	28	30	30
	Cooling		Silent operation	dBA	21	21	21	21
			Low	dBA	25	25	28	28
			High	dBA	37	37	42	42
			Nom.	dBA	31	31	35	35
Standard Accessories	Item				Installation manual	Installation manual	Installation manual	Installation manual
	Quantity				1	1	1	1
	Item				Operation manual	Operation manual	Operation manual	Operation manual
	Quantity				1	1	1	1
	Item				Wireless remote control			Wireless remote control
	Quantity				1			1
	Item				Batteries	Batteries	Batteries	Batteries
	Quantity				2	2	2	2
	Item				Remote control holder	Remote control holder	Remote control holder	Remote control holder
	Quantity				1	1	1	1
	Item				Mounting plate	Mounting plate	Mounting plate	Mounting plate
	Quantity				1	1	1	1
	Item				Indoor unit fixing screws	Indoor unit fixing screws	Indoor unit fixing screws	Indoor unit fixing screws
	Quantity				2	2	2	2
	Item				Titanium apatite photocatalytic air purification filter	Titanium apatite photocatalytic air purification filter	Titanium apatite photocatalytic air purification filter	Titanium apatite photocatalytic air purification filter
	Quantity				2	2	2	2
Control systems	Infrared remote control				ARC466A6	ARC466A6	ARC466A6	ARC466A6
Fan motor	Output		High	W	16			16
	Speed	Cooling	High	rpm	1,200	1,200	1,390	1,390
			Medium	rpm	990	990	1,120	1,120
			Low	rpm	780	780	850	850
			Silent operation	rpm	670	670	670	670
		Heating	High	rpm	1,290	1,290	1,430	1,430
			Medium	rpm	1,100	1,100	1,190	1,190

			Low	rpm	920	920	960	960
			Silent operation	rpm	690	690	690	690
				Steps	5 + silent, + auto	5 + silent, + auto	5 + silent, + auto	5 + silent, + auto
	Model				MM6C02J2VA	MM6C02J2VA	MM6C02J2VA	MM6C02J2VA
Heat exchanger	Fin		Type	ML fin (Multi louver)	ML fin (Multi louver)	ML fin (Multi louver)	ML fin (Multi louver)	ML fin (Multi louver)
	Fin pitch		mm	1.4	1.4	1.4	1.4	1.4
	Stages		Quantity	12	12	14	14	14
	Rows		Quantity	2	2	2	2	2
	Length		mm	610	610	610	610	610
	Tube type				ø7 Hi-XA	ø7 Hi-XA	ø7 Hi-XA	ø7 Hi-XA
Piping connections	Liquid	OD	mm	6.35	6.35	6.35	6.35	6.35
	Gas	OD	mm	9.5	9.5	9.5	9.5	9.5
	Drain				18	18	18	18
	Heat insulation				Both liquid and gas pipes	Both liquid and gas pipes	Both liquid and gas pipes	Both liquid and gas pipes
Power input	Cooling	Nom.	kW	0.040				0.040
	Heating	Nom.	kW	0.040				0.040
Sound power level	Cooling		dB(A)	55	55	59	59	59
	Heating		dB(A)	56	56	58	58	58
Air filter	Type				Removable / washable / mildew proof	Removable / washable / mildew proof	Removable / washable / mildew proof	Removable / washable / mildew proof
Dimensions	Packed unit	Width	mm	850	850	850	850	850
		Height	mm	346	346	346	346	346
		Depth	mm	274	274	274	274	274
	Unit	Width	mm	780	780	780	780	780
		Depth	mm	215	215	215	215	215
		Height	mm	289	289	289	289	289
Casing	Colour				White	White	White	White
Weight	Packed unit			kg	12	12	12	12
	Unit			kg	8	8	8	8
Fan	Air flow rate	Heating	Low	cfm	212	212	222	222
			High	m³/min	9.0	9.0	10.1	10.1
			Low	m³/min	6.0	6.0	6.3	6.3
			Silent operation	cfm	152	152	152	152
			Nom.	cfm	265	265	286	286
			Silent operation	m³/min	4.3	4.3	4.3	4.3
			High	cfm	318	318	357	357
			Nom.	m³/min	7.5	7.5	8.1	8.1
		Cooling	Low	m³/min	4.7	4.7	5.2	5.2

			Nom.	m ³ /min	6.3	6.3	7.2	7.2
			Low	cfm	166	166	184	184
			Silent operation	cfm	138	138	138	138
			Nom.	cfm	222	222	254	254
			High	m ³ /min	7.9	7.9	9.2	9.2
			High	cfm	279	279	325	325
			Silent operation	m ³ /min	3.9	3.9	3.9	3.9
	Type				Cross flow fan			Cross flow fan
Template					Split Sky Air Indoor	Split Sky Air Indoor	Split Sky Air Indoor	Split Sky Air Indoor
Air direction control					Right, Left, Horizontal, Downward	Right, Left, Horizontal, Downward	Right, Left, Horizontal, Downward	Right, Left, Horizontal, Downward
Temperature control					Microcomputer control	Microcomputer control	Microcomputer control	Microcomputer control
Power supply	Frequency			Hz	50	50	50	50
	Voltage			V	220-240	220-240	220-240	220-240
	Phase				1~	1~	1~	1~
Wiring connections - 50Hz	For power supply			Remark	3 for power supply, 4 for interunit wiring (Earth wire included)			3 for power supply, 4 for interunit wiring (Earth wire included)
Current	Nominal running current (RLA) - 50Hz	Heating	A	0.19 (1), 0.18 (2), 0.17 (3)	0.19 (3), 0.18 (4), 0.17 (5)	0.19 (3), 0.18 (4), 0.17 (5)	0.19 (1), 0.18 (2), 0.17 (3)	
		Cooling	A	0.19 (1), 0.18 (2), 0.17 (3)	0.19 (3), 0.18 (4), 0.17 (5)	0.19 (3), 0.18 (4), 0.17 (5)	0.19 (1), 0.18 (2), 0.17 (3)	
Notes					220V	220V	220V	220V
					230V	230V	230V	230V
					240V	240V	240V	240V
Standard Accessories	Item					Infrared remote control	Infrared remote control	
	Quantity					1	1	
Fan motor	Output	Rated	W		16	16		
Power input - 50Hz	Cooling	Nom.	kW		0.040	0.040		
	Heating	Nom.	kW		0.040	0.040		
Packing	Weight			kg		4		
Fan	Fan==Fan type					Cross flow fan	Cross flow fan	
Notes						SL: The silent fan level of the air flow rate setting	SL: The silent fan level of the air flow rate setting	
						When connected with multi-system outdoor unit, refer to the specifications of the multi outdoor unit to be connected.	When connected with multi-system outdoor unit, refer to the specifications of the multi outdoor unit to be connected.	