

				FTX20J3V1B	FTX25J3V1B	FTX35J3V1B	
Sound pressure level	Heating		High	dBA	39	40	41
			Nom.	dBA	34	34	35
			Silent operation	dBA	25	25	26
			Low	dBA	28	28	29
	Cooling		Silent operation	dBA	22	22	23
			Low	dBA	25	26	27
			High	dBA	39	40	41
			Nom.	dBA	33	33	34
Standard Accessories	Item			Installation manual	Installation manual	Installation manual	
	Quantity			1	1	1	
	Item			Operation manual	Operation manual	Operation manual	
	Quantity			1	1	1	
	Item			Infrared remote control	Infrared remote control	Infrared remote control	
	Quantity			1	1	1	
	Item			AA dry-cell batteries	AA dry-cell batteries	AA dry-cell batteries	
	Quantity			2	2	2	
	Item			Remote control holder	Remote control holder	Remote control holder	
	Quantity			1	1	1	
	Item			Mounting plate	Mounting plate	Mounting plate	
	Quantity			1	1	1	
	Item			Titanium apatite photocatalytic air purification filter	Titanium apatite photocatalytic air purification filter	Titanium apatite photocatalytic air purification filter	
	Quantity			2	2	2	
	Item			Indoor unit fixing screws	Indoor unit fixing screws	Indoor unit fixing screws	
	Quantity			2	2	2	
Refrigerant	Type			R-410A	R-410A	R-410A	
Control systems	Infrared remote control			ARC433A87	ARC433A87	ARC433A87	
Fan motor	Output		Rated	W	16	16	16
	Speed	Cooling	High	rpm	1,210	1,250	1,300
			Medium	rpm	990	1,030	1,070
			Low	rpm	780	820	850

			Silent operation	rpm	630	630	680
		Heating	High	rpm	1,260	1,300	1,340
			Medium	rpm	1,090	1,110	1,150
			Low	rpm	920	920	960
			Silent operation	rpm	820	820	850
				Steps	5 + silent, + auto	5 + silent, + auto	5 + silent, + auto
	Model				MM6C02J2VA	MM6C02J2VA	MM6C02J2VA
Power input - 50Hz	Cooling		Nom.	kW	0.030	0.030	0.030
	Heating		Nom.	kW	0.040	0.040	0.040
Packing	Weight			kg	4	4	4
Heat exchanger	Fin			Type	ML fin (Multi louver)	ML fin (Multi louver)	ML fin (Multi louver)
	Fin pitch			mm	1.4	1.4	1.4
	Stages			Quantity	14	14	14
	Rows			Quantity	2	2	2
	Length			mm	610	610	610
	Tube type				ø7 Hi-XA	ø7 Hi-XA	ø7 Hi-XA
Piping connections	Liquid		OD	mm	6.35	6.35	6.35
	Gas		OD	mm	9.5	9.5	9.5
	Drain				18	18	18
	Heat insulation				Both liquid and gas pipes	Both liquid and gas pipes	Both liquid and gas pipes
Sound power level	Cooling			dBA	55	55	58
	Heating			dBA	55	55	58
Air filter	Type				Removable / washable / mildew proof	Removable / washable / mildew proof	Removable / washable / mildew proof
Dimensions	Packed unit		Width	mm	846	846	846
			Height	mm	266	266	266
			Depth	mm	345	345	345
	Unit		Width	mm	770	770	770
			Depth	mm	198	198	198
			Height	mm	283	283	283
Casing	Colour				White	White	White
Weight	Packed unit			kg	11	11	11
	Unit			kg	7	7	7
Fan	Air flow rate	Heating	Low	cfm	222	222	235
			High	m³/min	9.4	9.7	10.1

			Low	m ³ /min	6.3	6.3	6.7
			Silent operation	cfm	194	194	201
			Nom.	cfm	276	283	295
			Silent operation	m ³ /min	5.5	5.5	5.7
			High	cfm	331	342	356
			Nom.	m ³ /min	7.8	8.0	8.4
		Cooling	Low	m ³ /min	5.9	6.0	6.1
			Nom.	m ³ /min	7.4	7.6	7.7
			Low	cfm	208	212	215
			Silent operation	cfm	166	169	173
			Nom.	cfm	261	268	272
			High	m ³ /min	9.1	9.2	9.3
			High	cfm	321	325	328
			Silent operation	m ³ /min	4.7	4.8	4.9
	Type				Cross flow fan	Cross flow fan	Cross flow fan
Template					Split Sky Air Indoor	Split Sky Air Indoor	Split Sky Air Indoor
Air direction control					Right, Left, Horizontal, Downward	Right, Left, Horizontal, Downward	Right, Left, Horizontal, Downward
Temperature control					Microcomputer control	Microcomputer control	Microcomputer control
Power supply	Frequency			Hz	50	50	50
	Voltage			V	220-240	220-240	220-240
	Phase				1~	1~	1~
Current	Nominal running current (RLA) - 50Hz		Heating	A	0.18	0.18	0.18
			Cooling	A	0.14	0.14	0.14
Notes	Notes--Description				SL: The silent fan level of the air flow rate setting	SL: The silent fan level of the air flow rate setting	SL: The silent fan level of the air flow rate setting