

| | | | | | | | | | | | |
|-----------------------------|---|----------------------------|-----------------------------|----|------|------|-------|-------|-------|-------|--|
| | | | Pdh (declared heating cap) | kW | 6.59 | 6.59 | 8.94 | 8.94 | 10.23 | 10.23 | |
| | | | COPd (declared COP) | | 1.92 | 1.92 | 2.52 | 2.52 | 1.53 | 1.53 | |
| | | | Power input | kW | 3.44 | 3.44 | 3.55 | 3.55 | 6.69 | 6.69 | |
| | | TBivalent | Tbiv (bivalent temperature) | °C | -7 | -7 | -7 | -7 | -7 | -7 | |
| | | | Pdh (declared heating cap) | kW | 5.60 | 5.60 | 10.00 | 10.00 | 10.00 | 10.00 | |
| | | | COPd (declared COP) | | 3.05 | 3.05 | 3.48 | 3.48 | 2.48 | 2.48 | |
| | | | Power input | kW | 1.84 | 1.84 | 2.88 | 2.88 | 4.04 | 4.04 | |
| | | A Condition (-7°C) | Pdh (declared heating cap) | kW | 5.60 | 5.60 | 10.00 | 10.00 | 10.00 | 10.00 | |
| | | | COPd (declared COP) | | 3.05 | 3.05 | 3.48 | 3.48 | 2.48 | 2.48 | |
| | | | Power input | kW | 1.84 | 1.84 | 2.88 | 2.88 | 4.04 | 4.04 | |
| | | B Condition (2°C) | Pdh (declared heating cap) | kW | 4.61 | 4.61 | 6.27 | 6.27 | 7.08 | 7.08 | |
| | | | COPd (declared COP) | | 3.73 | 3.73 | 3.65 | 3.65 | 3.67 | 3.67 | |
| | | | Power input | kW | 1.24 | 1.24 | 1.72 | 1.72 | 1.93 | 1.93 | |
| | | C Condition (7°C) | Pdh (declared heating cap) | kW | 2.91 | 2.91 | 4.11 | 4.11 | 4.70 | 4.70 | |
| | | | COPd (declared COP) | | 6.39 | 6.39 | 5.82 | 5.82 | 6.06 | 6.06 | |
| | | | Power input | kW | 0.46 | 0.46 | 0.71 | 0.71 | 0.78 | 0.78 | |
| | | D Condition (12°C) | Pdh (declared heating cap) | kW | 3.30 | 3.30 | 4.70 | 4.70 | 5.35 | 5.35 | |
| | | | COPd (declared COP) | | 7.29 | 7.29 | 6.74 | 6.74 | 6.97 | 6.97 | |
| | | | Power input | kW | 0.46 | 0.46 | 0.70 | 0.70 | 0.77 | 0.77 | |
| Pto (Thermostat off) | W | | | | 7.0 | 7.0 | 9.0 | 9.0 | 9.0 | 9.0 | |
| Cooling | | Psb (Standby mode cooling) | | W | 7.0 | 9.1 | 9.0 | 9.0 | 9.0 | 9.0 | |
| | | Cdc (Degradation cooling) | | | 0.25 | 0.25 | 0.25 | 0.25 | 0.25 | 0.25 | |
| Heating | | Psb (Standby mode heating) | | W | 7.0 | 9.1 | 9.0 | 9.0 | 9.0 | 9.0 | |
| | | Cdh (Degradation heating) | | | 0.25 | 0.25 | 0.25 | 0.25 | 0.25 | 0.25 | |
| Pck (Crankcase heater mode) | W | | | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | |
| Poff (Off mode) | W | | | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | |
| Cooling function included | | | | | Yes | Yes | Yes | Yes | Yes | Yes | |

| | | | | | | | | | | | |
|--|---------------------------|---------|------------------------------|-------------|--|-------------|---|-------------|---|-------------|---|
| Heating function included | | | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | |
| Average climate included | | | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | |
| Cold season included | | | | No | No | No | No | No | No | No | |
| Warm season included | | | | No | No | No | No | No | No | No | |
| Ecolabel logo | | | | No | No | No | No | No | No | No | |
| Template | | | | Sky Air Set | Sky Air Set | Sky Air Set | Sky Air Set | Sky Air Set | Sky Air Set | Sky Air Set | Sky Air Set |
| Cooling capacity | Nom. | | kW | | 6.8 | | 9.5 | | 12.0 | | 13.4 |
| Heating capacity | Nom. | | kW | | 7.5 | | 10.8 | | 13.5 | | 15.5 |
| Power input | Cooling | Nom. | kW | | 2.02 | | 2.49 | | 3.74 | | 4.17 |
| | Heating | Nom. | kW | | 2.06 | | 2.61 | | 3.65 | | 4.30 |
| Nominal efficiency | EER | | | | 3.37 | | 3.81 | | 3.21 | | 3.21 |
| | COP | | | | 3.64 | | 4.14 | | 3.70 | | 3.61 |
| Annual energy consumption | | | kWh | | 1,010 (0.000) | | 1,245 (0.000) | | 1,870 (0.000) | | 2,085 (0.000) |
| Energy labeling Directive | | Cooling | | | A | | A | | A | | |
| | | Heating | | | A | | A | | A | | |
| Seasonal efficiency (according to EN14825) | Heating (Average climate) | | Pdh Heating capacity at -10° | kW | | 5.98 | | | | | |
| Eurovent | Sound power level outdoor | Cooling | Nom. | dBA | | 64 | | | | | |
| | | Cooling | Nom. | dBA | | 55 | | | | | |
| Notes | | | | | Annual energy consumption is according to Energy labeling directive 2002/31/EC | | | | | | |
| | | | | | SEER and SCOP are according to EN 14825 | | | | | | |
| | | | | | | | EER/COP according to Eurovent 2012, for use outside EU only | | EER/COP according to Eurovent 2012, for use outside EU only | | EER/COP according to Eurovent 2012, for use outside EU only |
| | | | | | | | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load | | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load | | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load |