



				FBQ35D2VEB	FBQ50D2VEB	FBQ60D2VEB	FBQ71D2VEB	FBQ100D2VEB	FBQ125D2VEB	FBQ140D2VEB	
Casing	Colour			Not painted (galvanised)	Not painted (galvanised)	Not painted (galvanised)	Not painted (galvanised)	Not painted (galvanised)	Not painted (galvanised)	Not painted (galvanised)	
	Material			Galvanised steel plate	Galvanised steel plate	Galvanised steel plate	Galvanised steel plate	Galvanised steel plate	Galvanised steel plate	Galvanised steel plate	
Dimensions	Unit	Height	mm	245	245	245	245	245	245	245	
			Width	mm	700	700	1,000	1,000	1,400	1,400	1,400
			Depth	mm	800	800	800	800	800	800	800
	Packed unit	Height	mm	890	890	890	890	890	890	890	890
			Width	mm	900	900	1,200	1,200	1,600	1,600	1,600
			Depth	mm	295	295	295	295	295	295	295
Weight	Unit		kg	28	28	35	35	46	46	46	
	Packed unit		kg	30.5	30.5	38	38	49	49	49	
Heat exchanger	Fin	Type		Cross fin coil (Multi slit fins with hydrophilic treatment and Ø5Hi-XA tubes)	Cross fin coil (Multi slit fins with hydrophilic treatment and Ø5Hi-XA tubes)	Cross fin coil (Multi slit fins with hydrophilic treatment and Ø5Hi-XA tubes)	Cross fin coil (Multi slit fins with hydrophilic treatment and Ø5Hi-XA tubes)	Cross fin coil (Multi slit fins with hydrophilic treatment and Ø5Hi-XA tubes)	Cross fin coil (Multi slit fins with hydrophilic treatment and Ø5Hi-XA tubes)	Cross fin coil (Multi slit fins with hydrophilic treatment and Ø5Hi-XA tubes)	
Fan	Type			Sirocco fan	Sirocco fan	Sirocco fan	Sirocco fan	Sirocco fan	Sirocco fan	Sirocco fan	
	Quantity			1	1	2	2	3	3	3	
Air flow rate	Cooling	High	m³/min	15	15	18	18	29	34	34	
			Nom.	m³/min	12.5	12.5	15	15	26	29	29
			Low	m³/min	10.5	10.5	12.5	12.5	23	23.5	23.5
	Heating	High	m³/min	15	15	18	18	29	34	34	
			Nom.	m³/min	12.5	12.5	15	15	26	29	29
			Low	m³/min	10.5	10.5	12.5	12.5	23	23.5	23.5
External static pressure	High	Pa	150	150	150	150	150	150	150		
		Nom.	Pa	30	30	30	30	40	50	50	
Fan motor	Quantity			1	1	1	1	1	1	1	
	Model			Brushless DC motor	Brushless DC motor	Brushless DC motor	Brushless DC motor	Brushless DC motor	Brushless DC motor	Brushless DC motor	
	Speed	Steps		3	3	3	3	3	3	3	
	Output	Rated		W	130	130	230	230	300	300	300
	Poles			10	10	10	10	10	10	10	
Sound power level	Cooling		dBA	60	60	56	56	58	62	62	
Sound pressure level	Cooling	High	dBA	35	35	30	30	34	37	37	
			Nom.	dBA	32	32	28	28	32	35	35

