

				The power consumption for the valve motor is 5W (peak). This is only during opening.	The power consumption for the valve motor is 5W (peak). This is only during opening.	The power consumption for the valve motor is 5W (peak). This is only during opening.	The power consumption for the valve motor is 5W (peak). This is only during opening.	The power consumption for the valve motor is 5W (peak). This is only during opening.	The power consumption for the valve motor is 5W (peak). This is only during opening.	The power consumption for the valve motor is 5W (peak). This is only during opening.
				FWV01DAFN6V3/FV6V3	FWV02DAFN6V3/FV6V3	FWV03DAFN6V3/FV6V3	FWV04DAFN6V3/FV6V3	FWV06DAFN6V3/FV6V3	FWV08DAFN6V3/FV6V3	FWV10DAFN6V3/FV6V3
Water pressure drop	Cooling		kPa	13	13	11	12	14	12	19
	Heating		kPa	7	8	5	10	10	8	9
Sound power level	High		dB(A)	45	50	47	52	56	58	64
	Low		dB(A)	33	38	33	35	43	44	48
	Nom.		dB(A)	39	44	41	43	49	51	57
Air filter	Type			Plastic	Plastic	Plastic	Plastic	Plastic	Plastic	Plastic
Dimensions	Unit	Width	mm	774	774	984	1,194	1,194	1,404	1,404
		Depth	mm	226	226	226	226	226	251	251
		Height	mm	564	564	564	564	564	564	564
Water connections	Std. heat exchanger		inch	1/2	1/2	1/2	1/2	1/2	3/4	3/4
Water flow	Heating		l/h	196	182	286	396	465	694	816
	Cooling		l/h	251	327	494	745	803	1,142	1,355
Casing	Colour			Plastic and metal RAL9010	Plastic and metal RAL9010	Plastic and metal RAL9010	Plastic and metal RAL9010	Plastic and metal RAL9010	Plastic and metal RAL9010	Plastic and metal RAL9010
	Material			Plastic + sheet metal 3 (high, medium, low)	Plastic + sheet metal 3 (high, medium, low)	Plastic + sheet metal 3 (high, medium, low)	Plastic + sheet metal 3 (high, medium, low)	Plastic + sheet metal 3 (high, medium, low)	Plastic + sheet metal 3 (high, medium, low)	Plastic + sheet metal 3 (high, medium, low)
Fan motor	Speed		Steps	Closed induction, B class insulation, winding thermal cut-out	Closed induction, B class insulation, winding thermal cut-out	Closed induction, B class insulation, winding thermal cut-out	Closed induction, B class insulation, winding thermal cut-out	Closed induction, B class insulation, winding thermal cut-out	Closed induction, B class insulation, winding thermal cut-out	Closed induction, B class insulation, winding thermal cut-out
Weight	Unit		kg	20	21	26	32	33	44	44
	Air flow rate	Medium	m³/h	225	261	332	490	593	765	1,007
Fan		Low	m³/h	174	205	238	356	460	565	636
		High	m³/h	307	327	431	690	763	998	1,362
	Quantity			1	1	2	2	2	2	2
Cooling capacity	Total capacity	Nom.	kW	1.24 (1)	1.62 (1)	2.33 (1)	3.27 (1)	3.81 (1)	5.23 (1)	6.16 (1)
		High	kW	1.46 (1)	1.90 (1)	2.87 (1)	4.33 (1)	4.67 (1)	6.64 (1)	7.88 (1)
		Low	kW	0.99 (1)	1.35 (1)	1.73 (1)	2.48 (1)	3.11 (1)	3.93 (1)	4.07 (1)
	Sensible capacity	Low	kW	0.75 (1)	1.10 (1)	1.24 (1)	1.78 (1)	2.28 (1)	2.82 (1)	3.02 (1)
		High	kW	1.14 (1)	1.51 (1)	2.07 (1)	3.15 (1)	3.57 (1)	4.85 (1)	5.85 (1)
		Nom.	kW	0.97 (1)	1.25 (1)	1.66 (1)	2.45 (1)	2.87 (1)	3.80 (1)	4.57 (1)
Heat exchanger	Water volume		l	0.5	0.7	1	1.4	1.4	2.1	2.1
	Rows		Quantity	2	3	3	3	3	3	3
	Face area		m²	0.086	0.086	0.138	0.191	0.191	0.292	0.292
	Fin pitch		mm	1.8	1.6	1.6	1.8	1.6	2.1	2.1
	Stages		Quantity	10	10	10	10	10	12	12
Additional heat exchanger	Fin pitch		mm	1.6	1.6	1.6	1.6	1.6	1.6	1.6
	Face area		m²	0.068	0.068	0.11	0.152	0.152	0.243	0.243
	Water volume		l	0.2	0.2	0.3	0.4	0.4	0.6	0.6
	Stages		Quantity	8	8	8	8	8	10	10
	Rows		Quantity	1	1	1	1	1	1	
Piping connections	Drain	OD	mm	16	16	16	16	16	16	16
Heating capacity	4-Pipe	High	kW	1.90 (2)	2.10 (2)	3.08 (2)	5.05 (2)	5.30 (2)	7.91 (2)	9.30 (2)
		Medium	kW	1.70 (2)	1.78 (2)	2.68 (2)	4.25 (2)	4.65 (2)	6.83 (2)	7.95 (2)
		Low	kW	1.50 (2)	1.56 (2)	2.18 (2)	3.60 (2)	4.04 (2)	5.69 (2)	6.12 (2)
Power input	Nom.		W	28	36	43	61	68	104	130
	Low		W	21	24	29	38	47	76	90
	High		W	37	53	56	98	98	137	175
Vibration insulation				Rubber ring for fan motor	Rubber ring for fan motor	Rubber ring for fan motor	Rubber ring for fan motor	Rubber ring for fan motor	Rubber ring for fan motor	Rubber ring for fan motor
Insulation material				Class 1 self-extinguishing	Class 1 self-extinguishing	Class 1 self-extinguishing	Class 1 self-extinguishing	Class 1 self-extinguishing	Class 1 self-extinguishing	Class 1 self-extinguishing
Template				FCU	FCU	FCU	FCU	FCU	FCU	FCU
Current input	High		A	0.17	0.24	0.25	0.44	0.43	0.60	0.76
	Medium		A	0.13	0.16	0.20	0.29	0.31	0.46	0.58

